



The Public Health and Safety Organization

## NSF Product and Service Listings

These NSF Official Listings are current as of **Wednesday, March 08, 2017** at 12:15 a.m. Eastern Time. Please [contact NSF International](#) to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information:

<http://info.nsf.org/Certified/PwsComponents/Listings.asp?Company=0M760&Standard=061&>

### NSF/ANSI 61 Drinking Water System Components - Health Effects

**NOTE: Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. Click here for a list of [Abbreviations used in these Listings](#). Click here for the definitions of [Water Contact Temperatures denoted in these Listings](#).**

#### Satori Seal Company, Inc.

8455 Utica Avenue  
Rancho Cucamonga, CA 91730-3809  
United States  
800-322-8366  
909-987-8234

**Facility :** # 1 China

#### Joining and Sealing Materials

Trade Designation	Size	Water Contact Temp	Water Contact Material
<b>Gasket/Sealing Materials</b>			
E7014F	[2]	CLD 23	EPDM
E7014PXF[3]	1.0 sq. in./L	C. HOT	EPDM
N7014F[1]	2.0 sq. in/L	C. HOT	EPDM

[1] This material has also been evaluated for use in Mechanical Plumbing Device applications with a maximum surface area to volume ratio of 0.33 sq. in./L.

[2] Certified for a maximum surface area to volume ratio of 2.0 sq. in./L.

[3] This product has also been evaluated for use in Mechanical Plumbing Device applications with a maximum use restriction of 0.1 sq. in./L.

**O-Rings**

E7014F	[2]	C. HOT	EPDM
E7014PXF[3]	1.0 sq. in./L	C. HOT	EPDM
N7014F[1]	2.0 sq. in./L	C. HOT	NBR

[1] This material has also been evaluated for use in Mechanical Plumbing Device applications with a maximum surface area to volume ratio of 0.33 sq. in./L.

[2] Certified for a maximum surface area to volume ratio of 2.0 sq. in./L.

[3] This product has also been evaluated for use in Mechanical Plumbing Device applications with a maximum use restriction of 0.1 sq. in./L.

---

Number of matching Manufacturers is 1

Number of matching Products is 6

Processing time was 0 seconds