



The Public Health and Safety Organization

NSF Product and Service Listings

These NSF Official Listings are current as of **Monday, October 26, 2020** at 12:15 a.m. Eastern Time. Please [contact NSF](#) to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information:

<http://info.nsf.org/Certified/PwsComponents/Listings.asp?Company=C0314194&Standard=061&>

NSF/ANSI/CAN 61 Drinking Water System Components - Health Effects

NOTE: Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. [Click here for a list of Abbreviations used in these Listings.](#) [Click here for the definitions of Water Contact Temperatures denoted in these Listings.](#)

Satori Seal Corporation

8455 Utica Avenue

Rancho Cucamonga, CA 91730

United States

800-322-8366

909-987-8234

[Visit this company's website](#)

<http://www.santoriseal.com>

Facility : # 1 Vietnam

Joining and Sealing Materials

Trade Designation	Size	Water Contact Temp	Water Contact Material
Gasket/Sealing Materials			
E5012P-10[3]	[2]	C. HOT	EPI
E6012-45[4]	[2]	C. HOT	EPI
E7012-50IR[3]	[2]	C. HOT	EPI
E7012P-10[3]	[2]	D. HOT	EPI
E8012P-10[3]	[2]	C. HOT	EPI
N7012-20[1]	[2]	C. HOT	NBF
S6012F-00[3]	[2]	C. HOT	SLC

[1] This product has also been evaluated for use in Mechanical Plumbing De with a maximum use restriction of 0.1 sq. in./L.

[2] Certified for a maximum surface area to volume ratio of 2.0 sq. in./L.

[3] This product has also been evaluated for use in Mechanical Plumbing De with a maximum use restriction of 2.0 sq. in./L.

[4] This product has also been evaluated for use in Mechanical Plumbing De with a maximum use restriction of 0.4 sq. in./L.

O-Rings

E5012P-10[3]	[2]	C. HOT	EPI
E6012-45[4]	[2]	C. HOT	EPI
E7012-50IR[3]	[2]	C. HOT	EPI
E7012P-10[3]	[2]	D. HOT	EPI
E8012P-10[3]	[2]	C. HOT	EPI
N7012-20[1]	[2]	C. HOT	NBF
S6012F-00[3]	[2]	C. HOT	SLC

[1] This product has also been evaluated for use in Mechanical Plumbing De with a maximum use restriction of 0.1 sq. in./L.

[2] Certified for a maximum surface area to volume ratio of 2.0 sq. in./L.

[3] This product has also been evaluated for use in Mechanical Plumbing De with a maximum use restriction of 2.0 sq. in./L.

[4] This product has also been evaluated for use in Mechanical Plumbing De with a maximum use restriction of 0.4 sq. in./L.

Number of matching Manufacturers is 1

Number of matching Products is 14

Processing time was 0 seconds