



The Public Health and Safety Organization

## NSF Product and Service Listings

These NSF Official Listings are current as of **Monday, October 26, 2020** at 12:15 a.m. Eastern Time. Please [contact NSF](#) to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information:

<http://info.nsf.org/Certified/PwsComponents/Listings.asp?Company=C0449816&Standard=061&>

---

### NSF/ANSI/CAN 61 Drinking Water System Components - Health Effects

**NOTE: Unless otherwise indicated for Materials, Certification is only for the Water Contact Material shown in the Listing. [Click here for a list of Abbreviations used in these Listings.](#) [Click here for the definitions of Water Contact Temperatures denoted in these Listings.](#)**

---

#### Satori Seal Corporation

8455 Utica Avenue

Rancho Cucamonga, CA 91730-3809

United States

800-322-8366

909-987-8234

[Visit this company's website](#)

<http://www.SatoriSeal.com>

**Facility :** Yilan City, Taiwan

#### Joining and Sealing Materials

<b>Trade Designation</b>	<b>Size</b>	<b>Water Contact Temp</b>	<b>Water Contact Material</b>
<b>Gasket/Sealing Materials</b>			
E6015[1]	[2]	C. HOT	EPDM
E6515[1]	[2]	C. HOT	EPDM
E7015F[1]	[2]	C. HOT	EPDM
E7015F-08[3]	[2]	C. HOT	EPDM
E7015WRC[4]	[5]	C. HOT	EPDM
E8015[1]	[2]	C. HOT	EPDM
N5015	[6]	C. HOT	NBR
N6015	[6]	C. HOT	NBR
N7015F	[6]	C. HOT	NBR
N7515	[6]	C. HOT	NBR
N8015	[6]	C. HOT	NBR
S4015[7]	[8]	C. HOT	SLURRY
S6015[7]	[8]	C. HOT	SLURRY
S7015[7]	[8]	C. HOT	SLURRY
S8015[7]	[8]	C. HOT	SLURRY

[1] This product has also been evaluated for use in Mechanical Plumbing Device with a maximum use restriction of 0.2 sq. in./L.

[2] Certified for a maximum surface area to volume ratio of 2.0 square inches/L.

[3] This product is also evaluated for use in Mechanical Plumbing Device with a maximum use restriction of 1.1 square inches/L.

[4] This product has also been evaluated for use in Mechanical Plumbing Device with a maximum use restriction of 0.1 sq. in./L.

[5] Certified for a maximum surface area to volume ratio of 1 square inch/L.

[6] Certified for a maximum surface area to volume ratio of 1.6 sq. in./L.

[7] This product has also been evaluated for use in Mechanical Plumbing Device with a maximum use restriction of 0.15 square inches/L.

[8] Certified for a maximum surface area to volume ratio of 1.5 square inches/L.

---

Number of matching Manufacturers is 1

Number of matching Products is 15

Processing time was 0 seconds